

ROBO®SMART Monitoring – making bridge components intelligent




ROBO®SMART for Expansion Joints

ensuring safety and reducing life-cycle costs







mageba



Integrated smart system for expansion joints

Introduction

Bridge expansion joints compensate the deformations of a bridge relative to the ends of the bridge. They ensure the continuity of the carriageway (serviceability) whilst avoiding restraint loads. Their life expectancy depends on traffic loading, accumulated movements, climatic conditions, and above all the type of expansion joint and the quality of its design, fabrication and installation.

The use of a ROBO®SMART monitoring system can enable the life-cycle cost of an expansion joint to be optimised. Using such a system, the structure's behaviour can be assessed on the basis of continuously measured parameters, with data viewable online at any time of day or night.

mageba smart joints

mageba has an extensive track record of supplying structural health monitoring (SHM) systems for various applications, and is also a leading manufacturer of expansion joints for bridges and other structures. Combining the company's expertise in both fields enables it to now offer "smart" expansion joints. Any type of expansion joint from mageba's wide range can be designed and manufactured with an integrated SHM system - considerably simplifying its installation and reducing the total cost of ownership. Therefore, the potential use of an SHM system should ideally be considered already when specifying the expansion joint. Previously installed expansion joints can also be retrofitted with an SHM system where required.

- Small, self-powered and integrated acqui-
- Precise and durable sensors
- Robust electronics
- Data transfer via 3G GSM network
- 24-hour online data presentation via secure web interface

- Download of measured data
- Assembly on expansion joint in factory or on site


Sample benefits for the end user

- Measurement of accumulated movements leading to optimisation of maintenance intervals
- Warnings in case of passing of certain thresholds (e.g. movements, vibrations, rotations)
- Real-time availability of various parameters (e.g. structural and air temperature, bridge deck displacement, etc.)
- Measurement of maximum movements for expansion joint replacement projects, leading to optimised design of the new expansion joints based on actual required rotational and movement capacities





Vibration measurements on an expansion joint





Data check online





Installed expansion joint with displacement sensor

ROBO®SMART for expansion joints -Key data:

Measurements: Displacement, sliding

gap, inclination (max, min, accumulated),

Hardware: Sensors, acquisition

temperature

unit, 3G router, battery, solar panels, durable enclosures

Software: Secure web interface

Installation: Integrated ex-works

on joint, installation manual or complete installation by mageba on site

Accuracy: From 5mm to 0.01mm Frequency: From 1 value per hour

to 100Hz

Option:

Damage detection by automated vibration measurements, using additional high precision accelerometers at frequencies of up to 25.6kHz

mageba ROBO®CONTROL systems









engineering connections®

Permanent "BASIC"