

Certificate of constancy of performance

No. 0672-CPR-0924

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the

Construction Product(s)

Spherical Bearings with PTFE

with trade name

mageba Spherical Bearings with PTFE

placed on the market under the name or trade

mark of

Mageba Holding AG

Solistrasse 68 CH-8180 Bülach SWITZERLAND

produced in the manufacturing plant(s)

Mageba Turkey

Marmara Geri Dönüşümcüler San. Sit.

Şekerpınar Mah. Ayçiçeği Sk. No: 17, Çayırova / Kocaeli, Turkey

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

Annex ZA

of the standard(s)

EN 1337-7:2004

under system

1

for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 2021-05-11 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

This document has been translated for informative purpose only. Original version is issued in German. In any case of doubt the German version is valid.



5, Ge V





Dipl.-Ing. Siegfried Gerber Head of Certification Body

Materials Testing Institute University of Stuttgart

Annex 1

to the certificate of constancy of performance No. 0672-CPR-0924

Main performances for the construction product

Spherical Bearings with PTFE

with trade name

mageba Spherical Bearings with PTFE

with rotating element (calotte) and austenitic steel plate in the curved sliding surface, horizontal sliding part and external guides in case of unidirectional movable bearings, types 3.1, 3.3 and 3.5, see EN 1337-1:2001, minimum operation temperature of -35 °C to +48 °C, for use in building and civil engineering works where requirements on individual bearings are critical.

This Annex is only valid together with the certificate of constancy of performance 0672 - CPR - 0924.

