

Certificate of constancy of performance

No. 0672-CPR-0825

In compliance with *Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the

Construction Product(s) **Temporary Connection Devices (TCD)
Shock Transmission Unit (STU)
with trade name
RESTON®STU**

placed on the market
under the name or trade
mark of **mageba sa
Solistraße 68
CH-8180 Bülach
SWITZERLAND**

produced in the
manufacturing plant(s) **Mageba (Shanghai) Bridge Products Co., Ltd.
No. 388 BeiHuan Road, WuQiao Town, FengXiang District
201402 Shanghai, China**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

Annex ZA
of the standard(s) **EN 15129:2009**

under system **1**

for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on **2018-11-09** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

This document has been translated for informative purpose only. Original version is issued in German. In any case of doubt the German version is valid.

(Stamp)

Stuttgart, 2018-11-09

Dipl.-Ing. Siegfried Gerber
Head of Certification Body



Annex 1

to the certificate of constancy of performance No. 0672-CPR-0825

Main performances for the construction product:

Temporary Connection Devices (TCD)

Shock Transmission Unit (STU),

with trade name

RESTON®STU 240-250

according to EN 15129:2009, for use in buildings, bridges or civil engineering works where requirements on individual devices are critical.

This annex is valid for the following range:

Load capacity	192 to 288	kN
Stroke up to	250	mm
Construction and materials as type RESTON®STU 240-250		

RESTON®STU 240-250 main characteristics*:

Operating temperature	-80 to +60	°C
*These characteristics are not considered as a validity range criteria according to EN15129		

This Annex is only valid together with the certificate of constancy of performance according EU-BauPVO 0672-CPR-0825.

Stuttgart, 2018-11-09

(Stamp)

Annex 2

to the certificate of constancy of performance No. 0672-CPR-0825

Main performances for the construction product:

Temporary Connection Devices (TCD)

Shock Transmission Unit (STU),

with trade name

RESTON®STU 1500-100

according to EN 15129:2009, for use in buildings, bridges or civil engineering works where requirements on individual devices are critical.

This annex is valid for the following range:

Load capacity	1200 to 1800	kN
Stroke up to	100	mm
Construction and materials as type RESTON®STU 1500-100		

RESTON®STU 1500-100 main characteristics*:

Operating temperature	-80 to +60	°C
*These characteristics are not considered as a validity range criteria according to EN15129		

This Annex is only valid together with the certificate of constancy of performance according EU-BauPVO 0672-CPR-0825.

Stuttgart, 2018-11-09

(Stamp)