

Certificate of constancy of performance

No. 0672-CPR-0803

In compliance with *Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the

Construction Product(s) **Temporary (Dynamic) Connection Device (TCD)
with trade name
mageba Shock Transmission Unit RESTON® STU 600-100**

placed on the market
under the name or trade
mark of **mageba sa
Solistraße 68
CH-8180 Bülach
SWITZERLAND**

produced in the
manufacturing plant(s) **mageba Bridge Products Pvt. Ltd.
45, Jhowtala Road, 3rd Floor
700019 Kolkata, India**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

Annex ZA
of the standard(s) **EN 15129:2009**

under system **1**

for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on **2018-06-05** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

This document has been translated for informative purpose only. Original version is issued in German. In any case of doubt the German version is valid.



Stuttgart, 2018-06-05

Dipl.-Ing. Siegfried Gerber
Head of Certification Body



Annex 1

to the certificate of constancy of performance No. 0672-CPR-0803

Main performances for the construction product

Temporary (Dynamic) Connection Device (TCD)

with trade name

mageba Shock Transmission Unit RESTON® STU 600-100

according to EN 15129:2009, for use in building and civil engineering works where requirements on individual devices are critical.

Reaction force	480 to 720	kN
Maximal stroke	± 60	mm
activation velocity	≤ 5.0	mm/s
Operating temperature	-25 to +50	°C
Construction and materials as type RESTON® STU 600-100		

This Annex is only valid together with the certificate of constancy of performance according EU-BauPVO 0672 – CPR – 0803

Stuttgart, 2018-06-05

