

Certificate of constancy of performance

No. 0672-CPR-0955

In compliance with *Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the

Construction Product(s) **Isolators**
Elastomeric Bearings - Lead Rubber Bearings (LRB)
with trade name
mageba LASTO®LRB

placed on the market
under the name or trade
mark of **mageba Services & Technology AG**
Solistrasse 68
CH-8180 Bülach
SWITZERLAND

produced in the
manufacturing plant(s) **mageba Bridge Products Private Ltd.**
45, Jhowtala Road, 3rd Floor
700 019 Kolkata, India

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

Annex ZA
of the standard(s) **EN 15129:2009**
under system **1**

for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on **2021-12-16** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

This document has been translated for informative purpose only. Original version is issued in German. In any case of doubt the German version is valid.



S. Gerber

Dipl.-Ing. Siegfried Gerber
Head of Certification Body



Annex 1

to the certificate of constancy of performance No. 0672-CPR-0955

Main performances for the construction product

Elastomeric Isolators - Lead Rubber Bearings (LRB)

with trade name

mageba LASTO®LRB 600-152

according to EN 15129:2009, for use in building and civil engineering works where requirements on individual devices are critical.

External dimensions - Diameter	300 to 660	mm
External dimensions - Height	123 to 271	mm
Diameter of the internal reinforcing plates	295 to 649	mm
Shape factor of the elastomeric layers	16.6 to 20.2	-
Elastomeric compound (NR-rubber)	NR EN 60 20450	-
Service temperature range	-20 to +50	°C
Construction, attachment system (bolted anchoring plates) and manufacturing process as Type mageba LASTO®LRB 600-152		
Elastomer mixture and manufacturing process are deposited at the factory		

This Annex was issued on 2021-12-16 and is only valid together with the certificate of constancy of performance No. 0672-CPR-0955 according EU BauPVO.

Stuttgart, 2021-12-16

